

TOWER LIGHT

4 X 1000 W



Technical specification

GENERATOR	DCA25ESK
Frequency	50/60 Hz
Continuous Output Rating	20/25 kVA
Make & Model	Kubota V2203-KB
Lube Oil Sump Capacity	7.6 L
Coolant Capacity	7.9 L
Battery X Quantity	N70 X 1
Fuel tank capacity	62 L
Dry Weight	591 kg
7m dB (A) 1500/1800 rpm	62(50Hz), 64(60Hz)
BALLAST TYPE	H10CC23A (B) 50/EC
Supply Voltage	230 V
Frequency	50 Hz
Primary Wattage	1060 W
Primary Current	8.8 A
Lamp Current	7.5 A
FLOOD LIGHT	H562D
Inclination Angle	80° (Max Upward) 60° (Max Downward)
Weight	8.7 kg
Wattage	660 W up to 1000 W
METAL HALIDE LAMP	M1000LE/BUH
Power	1000 W
Lamp Voltage	145 V
Lamp Current	7.5 A
Approx Initial Lumens	90000 lm
Rated Average Life	9000 hrs
Burning Position	BUH ± 105°
DIMENSIONS	2500L X 1400W X 2500H mm
Max Height Including Travel distance	4500 mm
Total Weight	1200 kg